

Package: greenSD (via r-universe)

May 6, 2026

Type Package

Title Access and Analyze Global GreenSpace Spatial Data

Version 0.1.2

Description Access and analyze multi-band greenspace seasonality data cubes (available for 1,028 major global cities), global Normalized Difference Vegetation Index / land cover data from the European Space Agency WorldCover 10m Dataset, and Sentinel-2-L2a images. Users can download data using bounding boxes, city names, and filter by year or seasonal time window. The package also supports calculating human exposure to greenspace using a population-weighted greenspace exposure model introduced by Chen et al. (2022) [doi:10.1038/s41467-022-32258-4](https://doi.org/10.1038/s41467-022-32258-4) based on Global Human Settlement Layer population data, and calculating a set of greenspace morphology metrics at patch and landscape levels.

URL <https://github.com/billbillbilly/greenSD>,
<https://billbillbilly.github.io/greenSD/>

BugReports <https://github.com/billbillbilly/greenSD/issues>

License GPL-3

Encoding UTF-8

LazyData true

Depends R (>= 4.1)

Suggests testthat (>= 3.0.0), knitr, rmarkdown

VignetteBuilder knitr

Imports terra, maptiles, sf, future, furr, purrr, nominatimlite,
utils, cli, dsmSearch, rstac, landscapemetrics, magick, aws.s3,
dplyr, tidyr, stringr, tibble, grDevices, rlang

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Config/pak/sysreqs libabsl-dev cmake libfftw3-dev libfreetype6-dev libgdal-dev gdal-bin libgeos-dev libglpk-dev libglu1-mesa-dev make libmagick++-dev gsfonts texlive libicu-dev libjpeg-dev libpng-dev libtiff-dev libuv1-dev libxml2-dev libg11-mesa-dev libssl-dev libproj-dev libsqlite3-dev libudunits2-dev libx11-dev zlib1g-dev

Repository <https://billbillbilly.r-universe.dev>

Date/Publication 2025-11-07 08:51:39 UTC

RemoteUrl <https://github.com/billbillbilly/greensd>

RemoteRef HEAD

RemoteSha 7204c2a6134fa9202562cef649efbe1fec13153e

Contents

check_available_urban	2
check_urban_boundary	3
compute_exposure	4
compute_morphology	6
get_band_index_by_time	7
get_esawc	8
get_gsd	9
get_s2a_ndvi	10
get_tile_green	11
ndvi_to_sem	13
sample_values	14
to_gif	16

Index	17
--------------	-----------

check_available_urban *Get all of the urban areas in the Greenspace Seasonality Data Cube*

Description

This function returns all of the urban areas in the Greenspace Seasonality Data Cube dataset.

Usage

```
check_available_urban(test = FALSE)
```

Arguments

test logical. (ignored) Only for testing.

Value

dataframe

Note

You can explore all available urban areas in an interactive map at: https://github.com/billbillbilly/greenSD/blob/main/scripts/city_urban_boundaries.geojson

References

Wu, S., Song, Y., An, J. et al. High-resolution greenspace dynamic data cube from Sentinel-2 satellites over 1028 global major cities. *Sci Data* 11, 909 (2024). <https://doi.org/10.1038/s41597-024-03746-7>

Examples

```
check_available_urban(test = TRUE)
```

```
check_urban_boundary
```

Get an urban area boundary based on the UID

Description

This function returns a polygon of a city boundary based on the UID

Usage

```
check_urban_boundary(uid = NULL, plot = TRUE, test = FALSE)
```

Arguments

uid	numeric. Urban area ID. To check the ID of an available urban area, use check_available_urban()
plot	logical. Whether to plot city boundary
test	logical. (ignored) Only for testing.

Value

sf

References

Wu, S., Song, Y., An, J. et al. High-resolution greenspace dynamic data cube from Sentinel-2 satellites over 1028 global major cities. *Sci Data* 11, 909 (2024). <https://doi.org/10.1038/s41597-024-03746-7>

Examples

```
check_urban_boundary(test = TRUE)
```

compute_exposure *exposure*

Description

Computes population-weighted greenspace fraction or human exposure to greenspace based on a population-weighted exposure model (Chen et al., 2022), using population data from the Global Human Settlement Layer (GHSL; Pesaresi et al., 2024). See **Details** for the underlying method and assumptions.

Usage

```
compute_exposure(
  r = NULL,
  res = c(10, 10),
  pop_year = 2020,
  radius = 500,
  grid_size = NULL,
  height = FALSE,
  pop_out = FALSE,
  quiet = TRUE
)
```

Arguments

<code>r</code>	A <code>SpatRaster</code> with single/multiple greenspace layer(s), either fractional or binary (where non-green = 0 and green = 1), typically the output from <code>get_gsdc()</code> , <code>get_esa_wc()</code> , or <code>get_tile_green()</code> .
<code>res</code>	numeric vector of length 2. The actual spatial resolution (in meters). Default is <code>c(10, 10)</code> .
<code>pop_year</code>	numeric. Year of the GHSL dataset to use. Must be one of: 2015, 2020, 2025, or 2030. Default is 2020.
<code>radius</code>	numeric. Buffer radius (in meters) used for local averaging. Default is 500.
<code>grid_size</code>	numeric. Optional. If provided, output is aggregated to grid cells of this size (in meters) and returned as an <code>sf</code> object.
<code>height</code>	logical. Whether to compute greenspace volume for population-weighted greenspace fraction or human exposure to greenspace using Meta's global canopy height map (Tolan et al., 2024). (The default is <code>FALSE</code>)
<code>pop_out</code>	logical. Whether return population layer.
<code>quiet</code>	logical. Whether show progress bars for some process.

Details

This function implements the population-weighted greenspace exposure (PWGE) model:

1. Start with a population raster. Each pixel (i) has a population value (P_i) .
2. Create a circular buffer of radius (d) around each pixel center.
3. For each buffer, calculate greenspace fraction:

$$G_i^d = \frac{\text{Area of greenspace within buffer}}{\text{Total buffer area}}$$

4. Repeat for all $(i = 1, 2, \dots, N)$ grid cells.
5. Compute overall exposure:

$$GE^d = \frac{\sum_i P_i \cdot G_i^d}{\sum_i P_i}$$

Value

SpatRaster or sf. A SpatRaster (if grid_size is NULL) with layers pwgf_*, or an sf object with columns pwge_* representing population-weighted greenspace exposure values aggregated to each grid polygon.

References

Chen, B., Wu, S., Song, Y. et al. Contrasting inequality in human exposure to greenspace between cities of Global North and Global South. *Nat Commun* 13, 4636 (2022). <https://doi.org/10.1038/s41467-022-32258-4>

Pesaresi, M., Schiavina, M., Politis, P., Freire, S., Krasnodebska, K., Uhl, J. H., ... Kemper, T. (2024). Advances on the Global Human Settlement Layer by joint assessment of Earth Observation and population survey data. *International Journal of Digital Earth*, 17(1). <https://doi.org/10.1080/17538947.2024.2390454>

Tolan, J., Yang, H. I., Nosarzewski, B., Couairon, G., Vo, H. V., Brandt, J., ... & Couprie, C. (2024). Very high resolution canopy height maps from RGB imagery using self-supervised vision transformer and convolutional decoder trained on aerial lidar. *Remote Sensing of Environment*, 300, 113888.

Examples

```
sample_data <- terra::rast(system.file("extdata", "detroit_gs.tif", package = "greenSD"))
pwgf <- compute_exposure(
  # r = sample_data,
  pop_year = 2020,
  radius = 1500
)
```

compute_morphology *compute_morphology*

Description

Compute greenspace morphology metrics at patch (Nowosad & Stepinski, 2019) or landscape level (see details), including average size (AREA_MN), fragmentation (PD), connectedness (COHESION), aggregation (AI), and complexity of the shape (SHAPE_AM), related to public health (Wang et al., 2024)

Usage

```
compute_morphology(r = NULL, directions = 4, grid_size = NULL, quiet = TRUE)
```

Arguments

<code>r</code>	SpatRaster. A single-band binary greenspace raster, where 0 or NA represents non-green areas and 1 represents green areas.
<code>directions</code>	numeric. The number of directions in which patches should be connected: 4 (default) or 8.
<code>grid_size</code>	numeric or sf polygons. (Optional) If specified, morphology metrics at grid level will be computed based on the size (in meters) of given grid cells or input (sf) polygons.
<code>quiet</code>	logical. Whether show progress bars for some process.

Details

To get information of metrics, please use `landscapemetrics::list_lsm()`.

Value

A SpatVector object contains individual patches with metrics at patch level, when `grid_size = NULL`.

A SpatVector object contains landscape-level value of metrics, when `grid_size` is not NULL.

References

Nowosad J., TF Stepinski. 2019. Information theory as a consistent framework for quantification and classification of landscape patterns. <https://doi.org/10.1007/s10980-019-00830-x>

Wang, H., & Tassinary, L. G. (2024). Association between greenspace morphology and prevalence of non-communicable diseases mediated by air pollution and physical activity. *Landscape and Urban Planning*, 242, 104934.

Examples

```
green <- get_tile_green(  
  # bbox = c(-83.087174,42.333373,-83.042542,42.358748),  
  provider = "esri",  
  zoom = 16)  
# p <- terra::ifel(green$green == 0, NA, 1)  
m <- compute_morphology(  
  #r = p  
  directions = 8)
```

get_band_index_by_time

Get band index based on time period

Description

Converts a date string in "MM-DD" format to the corresponding band index for the Greenspace Seasonality Data Cube, which contains 36 bands representing 10-day intervals over a year.

Usage

```
get_band_index_by_time(time, year)
```

Arguments

time	Character vector of length 2. (optional) Start and end dates in "MM-DD" format (e.g., c("03-20", "10-15")). Used to subset the 10-day interval data cube by time.
year	numeric. (required) The year of interest.

Details

The Greenspace Data Cube is organized into 36 bands per year, each representing a 10-day interval. This function calculates which of those bands a given date falls into by converting the MM-DD string into the day-of-year (DOY) and dividing by 10 (rounded up).

Value

Interger. a band index.

Examples

```
get_band_index_by_time(c("03-20", "10-15"), year = 2020)
```

get_esa_wc	<i>Download landcover or NDVI Data from ESA WorldCover 10m Annual Dataset</i>
------------	---

Description

download 11-class landcover or 3-band NDVI Data (NDVI p90, NDVI p50, NDVI p10). Users can define an area of interest using a bounding box or place name.

Usage

```
get_esa_wc(
  bbox = NULL,
  place = NULL,
  datatype = "landcover",
  year = 2021,
  mask = TRUE,
  quiet = TRUE
)
```

Arguments

bbox	sf, sfc, or a numeric vector (xmin, ymin, xmax, ymax) defining the area of interest. Optional if place is provided.
place	character or vector. (optional) A single line address, e.g. ("1600 Pennsylvania Ave NW, Washington") or a vector of addresses (c("Madrid", "Barcelona")).
datatype	character. One of "landcover" and "ndvi".
year	numeric. The year of interest: 2020 or 2021. The default is 2021.
mask	logical (optional). Default is TRUE. If TRUE, masks the raster data using the given bbox or place.
quiet	logical. Whether show progress bars for some process.

Value

A SpatRaster object containing 11-class land cover or NDVI yearly percentiles composite (NDVI p90, NDVI p50, NDVI p10)

References

Zanaga, D., Van De Kerchove, R., De Keersmaecker, W., Souverijns, N., Brockmann, C., Quast, R., Wevers, J., Grosu, A., Paccini, A., Vergnaud, S., Cartus, O., Santoro, M., Fritz, S., Georgieva, I., Lesiv, M., Carter, S., Herold, M., Li, L., Tsendbazar, N.-E., ... Arino, O. (2021). ESA WorldCover 10 m 2020 v100 (Version v100). Zenodo. <https://doi.org/10.5281/zenodo.5571936>

Zanaga, D., Van De Kerchove, R., Daems, D., De Keersmaecker, W., Brockmann, C., Kirches, G., Wevers, J., Cartus, O., Santoro, M., Fritz, S., Lesiv, M., Herold, M., Tsendbazar, N.-E., Xu, P., Ramoino, F., & Arino, O. (2022). ESA WorldCover 10 m 2021 v200 (Version v200). Zenodo. <https://doi.org/10.5281/zenodo.7254221>

Examples

```
result <- get_esa_wc(
  # place = 'New York'
  year = 2021
)
```

get_gsd

Download Greenspace Seasonality Data Cube

Description

download Greenspace Seasonality Data Cube for an urban area. Retrieves high-resolution greenspace seasonality data from the Sentinel-2-based global dataset developed by Wu et al. (2024). Users can define a city of interest using a bounding box, place name, coordinates, or unique city ID (UID).

Usage

```
get_gsd(
  bbox = NULL,
  place = NULL,
  location = NULL,
  UID = NULL,
  year = NULL,
  time = NULL,
  mask = TRUE,
  quiet = TRUE
)
```

Arguments

bbox	sf, sfc, or a numeric vector (xmin, ymin, xmax, ymax) defining the area of interest. Optional if place, location, or UID is provided.
place	character or vector. (optional) A single line address, e.g. ("1600 Pennsylvania Ave NW, Washington") or a vector of addresses (c("Madrid", "Barcelona")). This can be ignored if location is specified.
location	vector or sf point. A point of interest. Ignored if UID is specified.
UID	numeric. Urban area ID. To check the ID of an available urban area, use check_available_urban()
year	numeric. (required) The year of interest.
time	Character vector of length 2 or character. (optional) Start and end dates in "MM-DD" format (e.g., c("03-20", "10-15") or "07-10"). Used to subset the 10-day interval data cube by time.
mask	logical (optional). Default is TRUE. If TRUE, masks the raster data using the given bbox or place if it is specified.
quiet	logical. Whether show progress bars for some process.

Details

The Greenspace Data Cube is organized into 36 bands per year, each representing a 10-day interval.

Value

A SpatRaster object containing the greenspace seasonality data.

Note

Use `check_available_urban()` and `check_urban_boundary()` to see supported cities and their boundaries.

References

Wu, S., Song, Y., An, J. et al. High-resolution greenspace dynamic data cube from Sentinel-2 satellites over 1028 global major cities. *Sci Data* 11, 909 (2024). <https://doi.org/10.1038/s41597-024-03746-7>

Examples

```
result <- get_gsdc(UID = 0,  
                  # year = 2022  
                  )
```

`get_s2a_ndvi`*Retrieve Sentinel-2-l2a images to compute NDVI*

Description

download Sentinel-2-l2a imagery data and compute NDVI. Users can define an area of interest using a bounding box or place name.

Usage

```
get_s2a_ndvi(  
  bbox = NULL,  
  place = NULL,  
  datetime = c(),  
  cloud_cover = 10,  
  vege_perc = 0,  
  select = "latest",  
  method = "first",  
  mask = TRUE,  
  output_bands = NULL,  
  quiet = TRUE  
)
```

Arguments

bbox	sf, sfc, or a numeric vector (xmin, ymin, xmax, ymax) defining the area of interest. Optional if place is provided.
place	character or vector. (optional) A single line address, e.g. ("1600 Pennsylvania Ave NW, Washington") or a vector of addresses (c("Madrid", "Barcelona")).
datetime	numeric vector of 2. The time of interest such as c("2020-08-01", "2020-09-01").
cloud_cover	numeric. Threshold for the percentage of cloud coverage. Default is 10.
vege_perc	numeric. Threshold for the percentage of vegetation coverage. Default is 0.
select	character. one of "latest", "earliest", "all". The default is "latest".
method	character. A method for mosaicing layers: one of "mean", "median", "min", "max", "modal", "sum", "first", "last". The default is "first".
mask	logical (optional). Default is TRUE. If TRUE, masks the raster data using the given bbox or place.
output_bands	vector. A list of band names (c('B04', 'B08')). The default is NULL. If output_bands is specified, NDVI will not be computed and only the specified bands will be returned. All available bands can be found here
quiet	logical. Whether show progress bars for some process.

Value

A SpatRaster object containing (multiple) NDVI layer(s) (for different period of time) select = "latest" or select = "first" (or if mask = TRUE and select = "all")

A List of NDVI rasters if mask = FALSE and select = "all".

Examples

```
result <- get_s2a_ndvi(
  # place = 'New York',
  datetime = c("2020-08-01", "2020-09-01")
)
```

get_tile_green

Classify greenspace based on map tile images

Description

Generate high-resolution greenspace segmentation using WorldImagery map tiles provided by esri and Sentinel-2 cloudless mosaic tiles provided by EOX.

Usage

```

get_tile_green(
  bbox = NULL,
  place = NULL,
  zoom = 17,
  provider = "esri",
  year = NULL,
  bright_filter = 0.85,
  gr_ratio_filter = 0.05,
  gb_ratio_filter = 0.05,
  clean = TRUE,
  quiet = TRUE
)

```

Arguments

bbox	sf, sfc, or a numeric vector (xmin, ymin, xmax, ymax) defining the area of interest. Optional if place is provided.
place	character or vector. (optional) A single line address, e.g. ("1600 Pennsylvania Ave NW, Washington") or a vector of addresses (c("Madrid", "Barcelona")).
zoom	numeric. Zoom level of map tile. The default is 17.
provider	character. One of "esri" and "eox".
year	integer. The desired year for Sentinel-2 cloudless mosaic tiles. (This is required when provider = "eox")
bright_filter	numeric. To remove very bright pixels (concrete, roofs, glare) Default is 0.85. With lower bright_filter, more bright pixels will be excluded.
gr_ratio_filter	numeric. (range from 0 to 1) To exclude pixels where green is only microscopically bigger than red. Default is 0.05. With higher gr_ratio_filter, more pixels will be excluded.
gb_ratio_filter	numeric. (range from 0 to 1) To exclude pixels where green is only microscopically bigger than blue. Default is 0.05. With higher gb_ratio_filter, more pixels will be excluded.
clean	logical. Whether to remove the blight and less green pixels based on bright_filter, gr_ratio_filter, and gb_ratio_filter.
quiet	logical. Whether show progress bars for some process.

Value

A list of two rasters including: greenspace segmentation (where 1 is green and 0 is non-green) and original map tiles

Note

The data derived from Esri WorldImagery may need to include appropriate Esri copyright notice.

Examples

```
g <- get_tile_green(
  # bbox = c(-83.087174, 42.333373, -83.042542, 42.358748),
  zoom = 15
)
```

ndvi_to_sem

ndvi_to_sem

Description

Convert ndvi raster data into semantic vegetation areas

Usage

```
ndvi_to_sem(r = NULL, threshold = c(0.2, 0.5), quiet = FALSE)
```

Arguments

<code>r</code>	A <code>SpatRaster</code> with single greenspace layer, typically the output from <code>get_esa_wc()</code> , or <code>get_s2a_ndvi()</code> .
<code>threshold</code>	numeric vector of two. Thresholds, defaulting to <code>c(0.2, 0.5)</code> , for classify two types of vegetation areas according to Hashim et al. (2019): (1) Non-vegetation (Development and bare land): NDVI values generally below 0.2. (2) Low vegetation (Shrub and grassland): NDVI values generally between 0.2 and 0.5. (2) High vegetation (Temperate and Tropical urban forest): NDVI values generally between 0.5 and 1.0.
<code>quiet</code>	logical. Whether show progress bars for some process.

Value

`SpatRaster`. A raster, where 0 represents non-green area, 1 represents shrub and grassland, and 2 represents trees.

References

Hashim, H., Abd Latif, Z., & Adnan, N. A. (2019). Urban vegetation classification with NDVI threshold value method with very high resolution (VHR) Pleiades imagery. *The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, 42, 237-240.

Examples

```
sample_data <- terra::rast(system.file("extdata", "detroit_gs.tif", package = "greenSD"))
seg <- ndvi_to_sem(sample_data$`25_NDVI`, threshold = c(0.2, 0.6))
```

sample_values	<i>Sample greenspace-related data from Greenspace Seasonality Data Cube, ESA WorldCover 10m Annual Composites Dataset, or Sentinel-2-12a images.</i>
---------------	--

Description

Samples values by locations from the Greenspace Seasonality Data Cube developed by Wu et al. (2024), ESA WorldCover 10m Annual Composites Dataset by Zanaga et al. (2021), or Sentinel-2-12a images.

Usage

```
sample_values(
  samples = NULL,
  time = NULL,
  source = "gsdc",
  output_bands = NULL,
  cloud_cover = 10,
  vege_perc = 0,
  select = "latest",
  method = "first",
  quiet = TRUE
)
```

Arguments

samples	A list, matrix, data.frame, or sf object of point locations. Can be a list of length-2 numeric vectors (<code>list(c(lon, lat))</code>), a 2-column matrix or data.frame, or an sf object with POINT geometry in any CRS.
time	numeric or vector. The time of interest. See Detail.
source	character. The data source for extracting greenspace values: <code>gsdc</code> for Greenspace Seasonality Data Cube (also see <code>get_gsdc()</code>), <code>esa_ndvi</code> or <code>esa_landcover</code> for ESA WorldCover 10m Annual Dataset (also see <code>get_esa_wc()</code>), and <code>s2a_ndvi</code> or <code>s2a_bands</code> for Sentinel-2-12a image data (also see <code>get_s2a_ndvi()</code>). The default is <code>gsdc</code> .
output_bands	vector. A list of band names (<code>c('B04', 'B08')</code>). The default is NULL. (Only required, when <code>source = "s2a_bands"</code>) All available bands can be found here
cloud_cover	numeric. The percentage of cloud coverage for retrieving Sentinel-2-12a images. (Only required, when <code>source = "s2a_ndvi"</code> or <code>source = "s2a_bands"</code>)
vege_perc	numeric. The percentage of cloud coverage for retrieving Sentinel-2-12a images. (Only required, when <code>source = "s2a_ndvi"</code> or <code>source = "s2a_bands"</code>)
select	character. one of "latest", "earliest", "all". The default is "latest".
method	character. A method for mosaicing layers: one of "mean", "median", "min", "max", "modal", "sum", "first", "last". The default is "first".
quiet	logical. Whether show progress bars for some process.

Details

time: For the greenspace seasonality data cube, only years from 2019 to 2022 are available. For ESA WorldCover 10m Annual Composites Dataset, only 2020 and 2021 are available.

Value

A data.frame containing greenspace values extracted at each point across all bands. Each row corresponds to a sample location; columns represent band values.

Note

For sampling data from Greenspace Seasonality Data Cube samples must be located within the same boundary of an available city in the data cube. Use `check_available_urban()` and `check_urban_boundary()` to see supported cities and their boundaries.

References

Wu, S., Song, Y., An, J. et al. High-resolution greenspace dynamic data cube from Sentinel-2 satellites over 1028 global major cities. *Sci Data* 11, 909 (2024). <https://doi.org/10.1038/s41597-024-03746-7>

Zanaga, D., Van De Kerchove, R., De Keersmaecker, W., Souverijns, N., Brockmann, C., Quast, R., Wevers, J., Grosu, A., Paccini, A., Vergnaud, S., Cartus, O., Santoro, M., Fritz, S., Georgieva, I., Lesiv, M., Carter, S., Herold, M., Li, L., Tsendbazar, N.-E., . . . Arino, O. (2021). ESA WorldCover 10 m 2020 v100 (Version v100). Zenodo. <https://doi.org/10.5281/zenodo.5571936>

Zanaga, D., Van De Kerchove, R., Daems, D., De Keersmaecker, W., Brockmann, C., Kirches, G., Wevers, J., Cartus, O., Santoro, M., Fritz, S., Lesiv, M., Herold, M., Tsendbazar, N.-E., Xu, P., Ramoino, F., & Arino, O. (2022). ESA WorldCover 10 m 2021 v200 (Version v200). Zenodo. <https://doi.org/10.5281/zenodo.7254221>

Examples

```
# see supported urban areas and their boundaries
check_available_urban()
boundary <- check_urban_boundary(uid = 11)

# sample locations with in the boundary
samples <- sf::st_sample(boundary, size = 20)

# extract values
gs_samples <- sample_values(samples,
                             # time = 2022
                             )
```

`to_gif`*Convert A Multi-layer Raster to GIF*

Description

Export a multi-layer raster (`SpatRaster`) or vector layer (`sf`) with multiple numeric value columns to an animated GIF.

Usage

```
to_gif(  
  r,  
  fps = 5,  
  width = 600,  
  height = 600,  
  axes = TRUE,  
  title_prefix = NULL,  
  border = FALSE  
)
```

Arguments

<code>r</code>	<code>SpatRaster</code> or <code>sf</code> . A <code>SpatRaster</code> with multiple layers or an <code>sf</code> object with multiple numeric value columns.
<code>fps</code>	numeric. Frames per second (default 5).
<code>width</code>	numeric. Width of output GIF in pixels.
<code>height</code>	numeric. Height of output GIF in pixels.
<code>axes</code>	logical. Draw axes?
<code>title_prefix</code>	character or character vector.
<code>border</code>	character. Color of polygon border(s); using NA hides them. Only optional when <code>r</code> is an <code>sf</code> object.

Value

An animated magick image object (GIF).

Examples

```
sample_data <- terra::rast(system.file("extdata", "detroit_gs.tif", package = "greenSD"))  
gif <- to_gif(sample_data)
```

Index

check_available_urban, 2
check_available_urban(), 3, 9, 10, 15
check_urban_boundary, 3
check_urban_boundary(), 10, 15
compute_exposure, 4
compute_morphology, 6

get_band_index_by_time, 7
get_esa_wc, 8
get_esa_wc(), 4, 13, 14
get_gsdc, 9
get_gsdc(), 4, 14
get_s2a_ndvi, 10
get_s2a_ndvi(), 13, 14
get_tile_green, 11
get_tile_green(), 4

ndvi_to_sem, 13

sample_values, 14

to_gif, 16